

TOUCAN-T


carpet manufacture

Xentral

Product specification (in accordance with DIN EN 1307)

also available as:

Pile material	(Directive 71/307/CEE modified)	100 % Polyamid solution dyed
Surface	(ISO 2424)	Loop Pile
Coloration	(ISO 2424)	mouliné
Wearability	(EN 1307)	commercial heavy (33) extreme
Comfort class	(EN 1307)	LC 1 (standard)



Performance properties



Environmental & Sustainability (***) in Beantragung

MVV TB	erfüllt die Anforderungen der MVV TB Anhang 8 + 9	
Gut - guidelines	erfüllt	www.gut-ev.de
PRODIS	Licence No.: ***	www.pro-dis.info
TÜV PROFICERT	Licence No.: ---	www.tuev-hessen.de
EPD (Environmental Product Declaration)	EPD-GUT-2009211-D	www.bau-umwelt.com Institut Bauen und Umwelt e.V.

Characteristic features

Width	(ISO 3018)	400 cm
Primary backing	(ISO 2424)	PP-fabric
Secondary backing	(ISO 2424)	synthetic textile backing
Total weight	(ISO 8543)	ca. 1.650 g/m ²
Total height	(ISO 1765)	ca. 5,5 mm
Pile weight	(manufacturer information)	ca. 550 g/m ²

Structural properties

Fire behaviour	(EN 13501-1)	Cfl-s1 verklebt
Electrostatic properties	(EN 1815)	≤ 2 KV
Surface resistance	(ISO/DIS 10965)	≤ 10 ⁸ Ω
Volume resistance	(ISO/DIS 10965)	≤ 10 [#] Ω

Color fastness values

Light fastness	(ISO 105-B02)	≥ 5
Rubbing fastness	(EN ISO 105-X12)	≥ 3 / ≥ 3-4
Water fastness	(EN ISO 105-E01)	≥ 4

Last revision 07/2018

We reserve the right for technical changes while maintaining the service properties of the carpet

TOUCAN-T GmbH
Carpet Manufacture

St. Töniser Str. 84
D - 47803 Krefeld

Fon +49 (0) 21 51 / 84 19-0
Fax +49 (0) 21 51 / 84 19-99

service@toucan-t.de
www.toucan-t.de