




 **MADE IN THE UK. MADE TO LAST.**

## Specification

<b>PRODUCT</b>	Array Heavy Contract Fibre Bonded Tiles and Planks
<b>FIBRE CONSTRUCTION</b>	85% Polypropylene, 15% Polyamide
<b>WEIGHT</b>	4075gsm (Tile and Plank)
<b>THICKNESS</b>	8.50mm
<b>TILE SIZE</b>	 50cm x 50cm (Tiles are Bitumen backed)
<b>PLANK SIZE</b>	 100cm x 25cm (Planks are Bitumen backed)
<b>TILES PER BOX</b>	16 (4m <sup>2</sup> )
<b>PLANKS PER BOX</b>	14 (3.5m <sup>2</sup> )
<b>COLOUR FASTNESS</b>	Light (BS EN ISO 105:B02) >6 Wet Rubbing (BS EN ISO 105:X12) 4-5 Dry Rubbing (BS EN ISO 105:X12) 4-5
<b>FLAMMABILITY</b>	(BS5287) Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char
<b>BS EN 13501</b>	Class Bfl-s1 (Tile) Class Cfl-s1 (Plank)
<b>REDUCTION IN IMPACT NOISE</b>	BS EN ISO 140-8: 22dB
<b>ANTISTATIC</b>	Suitable for use in computer rooms
<b>INSTALLATION</b>	 Tiles Array tiles should be laid tessellated as per the icon provided. The method of installation should conform to BS5325. For details of subfloor preparation and a full guide to installation visit: <a href="http://www.heckmondwike-fb.co.uk">www.heckmondwike-fb.co.uk</a> . Before laying Array, tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels.
<b>ADHESIVE GUIDE</b>	Use F.Ball F41 or Bostik Laybond Carpet Tile Tackifier
<b>MAINTENANCE</b>	To achieve maximum life expectancy it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: <a href="http://www.heckmondwike-fb.co.uk">www.heckmondwike-fb.co.uk</a>

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Heckmondwike reserves the right to change or modify product specifications without giving prior notice.



This Heckmondwike product is EPD verified in accordance with ISO 14025 and EN15804.



11/22