

RIGID CLICK

Features	Standard	Planks
Floorcovering	EN 649	Heterogeneous LVT floorcovering
Completion		Matte particle lacquer
Design		Wood / stone
Embossing		Hout: Registered / universal Embossed Stone: Overall Embossed
Colors		14 / 6
Backing		Click on cork
Measurements planks	EN 427	Wood: 151,8 x 23,6 cm 121,3 x 22,2 cm Stone: 45,1 x 90,8 cm
Bevelling		aan alle zijden
Packaging		Wood: 6 pieces (2.139 m ²) 6 pieces (1.617 m ²) Stone: 4 pieces (1.638 m ²)
Weight	EN 430	ca. 9600 g/m ²
Total thickness	EN 428	6,0 mm
Thickness PU lacquer	EN 429	0,55 mm
Classification	EN 685	23, 33, 42
Fire classification	EN 13501	Bfl-S1
Slipresistance	DIN 51130 EN 13893	R10 DS
Weargroup	EN 649	T
Residual indentation	EN 433	< 0,1 mm
Dimension stability	EN 434	< 0,1%
Soundreduction	EN140-8	ca. 10 dB(A)
Thermal conductivity	EN12667 DIN 52612	0,049 m ² k/w
Electrical Conductivity	EN 1081	app 10 ¹¹ Ohm
Suitable for castor chairs	EN 425	Yes, type W
Floor heating	EN14041	Yes, max. 27°C
Colourfastness	ISO 105-B02	6> Grade
Resistance to chemicals	EN 423 EN ISO 26987	Yes, see 1
Odor control	ISO 16000-28	Suisse Norm SNV
AgBB VOC test		Approved
REACH regulation (EC)		1907/2006
CE, AGBB, Dibt, Eurofins, Floorscore, A+, ISO9001, ISO14001		Yes

¹Resistance depending on concentration and exposure time, with prolonged action of oils, fats, acids, alkalis and other aggressive chemicals please contact us.

