

# CHEVRON SERIES

Eigenschappen	Norm	
Floorcovering	EN 649	Heterogeneous LVT floorcovering
Completion		Matte particle laquer
Design		Wood
Embossing		Registered Embossed
Colors		4
Measurements planks	EN 427	11,43 x 57,15 cm (chevron) 15,24 x 60,96 cm (herringbone) 22,8 x 121,9 cm (planks)
Bevelling		aan alle zijden
Packaging		52 pieces (3.397 m <sup>2</sup> ) (chevron) 36 pieces (3.345 m <sup>2</sup> ) (herringbone) 12 pieces (3.345 m <sup>2</sup> ) (planks)
Weight	EN 430	ca. 4315 g/m <sup>2</sup>
Total thickness	EN 428	2,5 mm
Thickness PU lacquer	EN 429	0,55 mm
Classification	EN 685	23, 33, 42
Fire classification	EN 13501	Bfl-S1
Slipresistance	DIN 51130 EN 13893	R9 DS
Weargroup	EN 649	T
Residual indentation	EN 433	< 0,1 mm
Dimension stability	EN 434	< 0,1%
Soundreduction	EN140-8	ca. 5 dB(A)
Thermal conductivity	EN12667 DIN 52612	0,02 m <sup>2</sup> k/w
Electrical Conductivity	EN 1081	app 10 <sup>11</sup> Ohm
Suitable for castor chairs	EN 425	Yes, type W
Floor heating	EN14041	Yes, max. 27°C
Colourfastness	ISO 105-B02	6> Grade
Resistance to chemicals	EN 423 EN ISO 26987	Yes, see 1
Odor control	ISO 16000-28	Suisse Norm SNV
AgBB VOC test		Approved
REACH regulation (EC)		1907/2006
CE, AGBB, Dibt, Eurofins, Floorscore, A+, ISO9001, ISO14001		Yes

<sup>1</sup>Resistance depending on concentration and exposure time, with prolonged action of oils, fats, acids, alkalis and other aggressive chemicals please contact us.

