### technical specifications

**Product Name Product Description Pile Yarn Description** Tile Dimensions **Pile Yarn Weight Total Weight Pile Height Total Thickness** Gauge/ends per 10cm Tufts per m2 / Pile Density **Backing Description** Wear Classification Luxury Rating Class Flammability **Thermal Resistance Castor Chair Rating** Hexapod Static Loading **Dynamic Loading Body Voltage Test Colour Fastness To Light Colour Fastness To Shampoo** Sound Absorption Coefficient **Reduction in Impact Noise** Reduction in Impact Noise at 1000Hz Number Of Tiles Per Box

Balance Grid, Balance Ground, Balance Grade **Multilevel Loop** 100% Solution Dyed Nylon 6 (Polyamide-PA) 50 cm x 50 cm 628g/m<sup>2</sup> 4028g/m<sup>2</sup> 4.5mm 7.0m 1/12th gauge 48 stitches 226,771/m<sup>2</sup> Accummen<sup>™</sup>, 75% recycled BS EN 1307 Heavy Commercial Use Class 33 LC2 **Euroclass Bfl-s1** Tog Rating: 0.42 BS EN 985 Pass - suitable for continuous use BS ISO 10361: Method B:2000 3 to 4 BS 4939: 1987 (2003) Recovery >80% (24hrs) BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts) BS ISO 6356:2000 <2kV BS EN ISO 105 - BO2 Minimum Grade 6 BS 1006:UK-TB: 1990 Minimum Grade 4-5 BS EN 354:2003 BS EN ISO 10140-3:2010 23dB BS EN ISO 10140-3:2010 36.3dB 20 (5m2)

For best results we recommend

1	1		
1	1		
Monolithic			



¢İ.









Certificate Number FM01 BS EN ISO 9001:2015



of volatile substances in indoor air posing a toxic threat during inhaling – on a scale from A+ (very low-emission) to C (highemission)



Environmental Product Declaration by independent third-party verification of the declaration and data, according to ISO 14025:2006

#### environmental information

- burmatex® products are EPD verified by an independent third-party verification of the declaration and data, according to ISO 14025:2006. For specific ratings, please refer to www.environdec.com
- $\ensuremath{\mathsf{burmatex}}\xspace^{\ensuremath{\mathbb{R}}}$  products qualify for SKA as they achieve one or more requested criteria
- burmatex® products can contribute to the WELL Building Standard<sup>™</sup>, which focuses on the people and healthy workspaces
- All burmatex® carpet/carpet tile/carpet plank ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of burmatex  $\ensuremath{\mathbb{R}}$  AccummenTM backing comes from recycled materials
- Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- All manufacturing waste is recycled and all electricity used is from renewable resources
- All burmatex® products are heavy contract with a 10 year guarantee for maximum useful life
- Certified, Class A+: very-low VOC Emission

Burmatex Ltd Victoria Mills, The Green Ossett, West Yorkshire WF5 OAN United Kingdom T +44 (0) 1924 262 525 F +44 (0) 1924 280 033 UK email: projects@burmatex.co.uk International email: international@burmatex.co.uk www.burmatex.co.uk Burmatex reserves the right to improve the specification of all products without prior notification. E&OE

Burmatex carpets and carpet tiles should be installed and used in full accordance with instructions at www.burmatex. co.uk and recognised trade standards.

Orders are subject to Burmatex terms and conditions of sale. See: www.burmatex.co.uk

## LRV values for **balance grid**

Product code	Product colour name	CIE Y	CIE L
33901	steel grey	12.70	42.06
33902	warm dusk	21.06	53.08
33903	concrete core	18.14	50.18
33904	granite mesh	21.40	54.39
33905	smokey clay	13.64	43.19
33906	skylight chrome	13.82	44.52
33907	harbour cloud	13.26	41.73
33908	black nickel	6.73	29.39
33909	river haze	8.86	36.58
33910	sage glass	9.68	37.56
33911	twilight fog	9.34	35.52
33912	navy night	5.76	27.46

# LRV values for **balance ground**

Product code	Product colour name	CIE Y	CIE L
34101	steel	7.96	35.38
34102	warm	14.53	45.10
34103	concrete	15.01	45.30
34104	granite	16.15	47.16
34105	clay	17.94	50.00
34106	skylight	8.85	35.40
34107	harbour	8.05	32.91
34108	nickel	9.30	36.22
34109	river	6.15	28.31
34110	sage	14.46	45.64
34111	twilight	5.61	29.52
34112	navy	3.66	22.33

# LRV values for **balance grade**

Product code	Product colour name	CIE Y	CIE L
34001	steel tower	11.76	40.71
34002	warm frost	21.16	53.29
34003	concrete lead	18.38	50.68
34004	granite vapour	22.10	54.52
34005	city clay	11.32	40.85
34006	skylight beam	12.78	43.09
34007	harbour view	12.19	40.18
34008	urban nickel	6.25	29.21
34009	river dew	7.93	32.06
34010	sage vista	9.57	36.17
34011	twilight dawn	8.64	35.09
34012	navy shore	5.88	27.58