






6958



6959



6960



6961




6957



6956



6950



6962



6955



6951



6963



6954



6953



6952



6964



Strapazierwert 32 - normal (intensive) | **Komfortwert** LC5 prestige | **Herstellungsart** getuftet | **Verwendungsbereich** Stuhlrolle | **Material der Nutzschicht** 100 % PA Alto® | **Poleinsatzgewicht** ca. 1.830 g/m² | **Brandverhalten** Cfl-s1
Wear criteria 32 - normal (intensive) | **Comfort criteria** LC5 prestige | **Method of Production** tufted | **Application** Chair castor | **Pile material** 100 % PA Alto® | **Pile weight** approx. 1.830 g/m² | **Fire behaviour** Cfl-s1

Alle TOUCAN-T Qualitäten erfüllen die Anforderungen für LEED und DGNB zertifizierte Gebäude.
 All TOUCAN-T products fulfill the requirements for LEED and DGNB certified buildings.

TOUCAN-T

carpet manufacture


Unisono

version



Product specification (in accordance with DIN EN 1307)

Pile material	(Directive 71/307/CEE modified)	100 % Polyamide Alto®
Surface	(ISO 2424)	Cut Pile
Coloration	(ISO 2424)	uni
Wearability	(EN 1307)	commercial intensive (32) heavy
Comfort class	(EN 1307)	LC 5 (prestige)



Performance properties



Environmental & Sustainability

DIBt-AgBB Schema	AbZ.: Z-156.601-22
Gut - guidelines	fulfilled (Prodis)
PRODIS	Licence No.: D88DBDF5
TÜV PROFICERT	Licence No.: 70 710 3720-1
EPD (Environmental Product Declaration)	EPD-GUT-2009211-D

www.dibt.de
www.gut-ev.de
www.pro-dis.info
www.tuev-hessen.de
www.bau-umwelt.com

TOUCAN-T is member of:



Institut Bauen und Umwelt e.V.

Characteristic features

Width	(ISO 3018)	400 cm
Primary backing	(ISO 2424)	PP-fabric
Secondary backing	(ISO 2424)	synthetic textile backing
Total weight	(ISO 8543)	ca. 2.800 g/m ²
Total height	(ISO 1765)	ca. 11,5 mm
Pile weight	(manufacturer information)	ca. 1.830 g/m ²

Structural properties

Fire behaviour	(EN 13501-1)	Cfl-s1
Electrostatic properties	(EN 1815)	≤ 2 KV
Surface resistance	(ISO/DIS 10965)	≤ 10 ⁹ Ω
Volume resistance	(ISO/DIS 10965)	≤ 10 ⁹ Ω

Color fastness values

Light fastness	(ISO 105-B02)	≥ 5
Rubbing fastness	(EN ISO 105-X12)	≥ 3 / ≥ 3-4
Water fastness	(EN ISO 105-E01)	≥ 4

Last revision 09/2013-1

We reserve the right for technical changes while maintaining the service properties of the carpet

TOUCAN-T GmbH
Carpet Manufacture

St. Töniser Str. 84
D - 47803 Krefeld

Fon +49 (0) 21 51 / 84 19-0
Fax +49 (0) 21 51 / 84 19-99

service@toucan-t.de
www.toucan-t.de