technical specifications

Product Name

Product Description

Pile Yarn Description 100% Solution Dyed Nylon 6.6 (Polyamide-PA)

Tile Dimensions Pile Yarn Weight **Total Weight** Pile Height **Total Thickness**

Gauge/ends per 10cm Tufts per m2 / Pile Density

Backing Description

Wear Classification **Luxury Rating Class**

Flammability

Thermal Resistance **Castor Chair Rating**

Hexapod Static Loading

Dynamic Loading Body Voltage Test

Colour Fastness To Light Colour Fastness To Shampoo Sound Absorption Coefficient

Reduction in Impact Noise Reduction in Impact Noise at 1000Hz

Number Of Tiles Per Box

Hadron

Textured Level Loop

50 cm x 50 cm 800g/m² +/-10% 4240g/m² +/-10% 3.5mm +/-10% 6.5mm +/-10%

1/10th gauge 45 stitches

177,165/m² +/-10%

Accummen™, 75% recycled

BS EN 1307 Heavy Commercial Use Class 33

LC₂

Euroclass Bfl-s1

Tog Rating 0.30; ISO 8302: 0.05 m²K/W BS EN 985 Pass - suitable for continuous use

BS ISO 10361: Method B:2000 3 to 4

BS 4939: 1987 (2003) Recovery >80% (24hrs)

BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)

BS ISO 6356:2000 <2kV

BS EN ISO 105 - B02 Minimum Grade 6 BS 1006:UK-TB: 1990 Minimum Grade 4-5

BS EN 354:2003

BS EN ISO 10140-3:2010 23dB BS EN ISO 10140-3:2010 37dB

20 (5m²)

For best results we recommend





























Environmental Profiles





Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling - on a scale from A-(very low-emission) to C (high-



The Building Information Foundation, Finland. Certified building materials with low emission class M1

environmental information

- Burmatex products achieve either A or A+ across all the BREEAM defined building applications For specific rating, please refer to www.breeam.co.uk
- Burmatex products qualify for SKA as they achieve one or more requested criteria
- All Burmatex carpet/carpet tile ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of Burmatex Accummen[™] backing comes from recycled materials
- Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- · All manufacturing waste is recycled and all electricity used is from renewable resources
- · All Burmatex products are heavy contract with a 10 year guarantee for maximum useful life
- Certified, Class A+: very-low VOC Emission

LEED® v4 - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/CI-v4 MRc2/MRc3 (Building product disclosure and optimization - environmental product declarations), MRc3/MRc4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/contact

Burmatex Ltd Victoria Mills, The Green Ossett, West Yorkshire WF5 OAN **United Kingdom**

T +44 (0) 1924 262 525 F +44 (0) 1924 280 033

UK email: projects@burmatex.co.uk

International email: international@burmatex.co.uk www.burmatex.co.uk

Burmatex reserves the right to improve the specification of all products without prior notification. E&OE Burmatex carpets and carpet tiles should be installed and used

in full accordance with instructions at www.burmatex.co.uk and recognised trade standards.

Orders are subject to Burmatex terms and conditions of sale. See: www.burmatex.co.uk

LRV values for **hadron**

Product code	Product colour name	CIE Y	CIE L
21601	titanium	1.93	15.12
21602	cerulean	2.67	18.65
21603	sparkler	2.54	18.10
21604	firefly	3.27	21.10
21605	crimson	2.31	17.03
21606	papaya	2.51	17.95
21607	flamingo	2.22	16.61
21608	moss	2.28	16.87
21609	mint	2.22	16.62
21610	clay	2.52	18.00
21611	starling	2.28	16.89
21612	raspberry	2.26	16.79
21613	rust	2.08	15.90
21614	violet	2.13	16.15
21615	ash	2.39	17.40
21616	arctic	2.33	17.15
21617	electric	2.03	15.67