

STONE SERIES

Features	Standard	Tiles
Floorcovering	EN 649	Heterogeneous LVT floorcovering
Completion		Matte particle lacquer
Design		Concrete / Amato / Rustique
Embossing		Universal Embossed
Colors		14
Measurements planks	EN 427	45,72 x 91,44 cm 91,44 x 91,44 cm 100 x 100 cm
Bevelling		all sides
Packaging		45,72 x 91,44 cm: 9 pieces (3.763 m ²) 91,44 x 91,44 cm: 5 pieces (4.181 m ²) 100 x 100 cm: 4 pieces (4 m ²)
Weight	EN 430	ca. 4315 g/m ²
Total thickness	EN 428	2,5 mm
Thickness PU lacquer	EN 429	0,55 mm
Classification	EN 685	23, 33, 42
Fire classification	EN 13501	Bfl-S1
Slipresistance	DIN 51130 / EN 13893	R9 / DS
Weargroup	EN 649	T
Residual indentation	EN 433	< 0,1 mm
Dimension stability	EN 434	< 0,1%
Soundreduction	EN140-8	ca. 5 dB(A)
Thermal conductivity	EN12667 DIN 52612	0,02 m ² k/w
Electrical Conductivity	EN 1081	app 10 ¹¹ Ohm
Suitable for castor chairs	EN 425	Yes, type W
Floor heating	EN14041	Yes, max. 27°C
Colourfastness	ISO 105-B02	6> Grade
Resistance to chemicals	EN 423 EN ISO 26987	Yes, see 1
Odor control	ISO 16000-28	Suisse Norm SNV
AgBB VOC test		Approved
REACH regulation (EC)		1907/2006
CE, AGBB, Dibt, Eurofins, Floorscore, A+, ISO9001, ISO14001		Yes

¹Resistance depending on concentration and exposure time, with prolonged action of oils, fats, acids, alkalis and other aggressive chemicals please contact us.

