technical specifications

Product Name Product Description Pile Yarn Description Tile Dimensions Pile Yarn Weight **Total Weight** Pile Height **Total Thickness**

Gauge/ends per 10cm Tufts per m2 / Pile Density

Backing Description Wear Classification **Luxury Rating Class** Flammability

Thermal Resistance **Castor Chair Rating**

Hexapod Static Loading **Dynamic Loading Body Voltage Test** Colour Fastness To Light Colour Fastness To Shampoo Sound Absorption Coefficient

Reduction in Impact Noise Reduction in Impact Noise at 1000Hz

Number Of Tiles/Planks Per Box

Tivoli Mist Low Level Loop

100% Solution Dyed Nylon (Polyamide-PA) 50 cm x 50 cm, 25 cm x 100 cm (planks)

600g/m² +/-10% 4050g/m² +/-10% 4.0mm +/-10% 6.5mm +/-10%

1/10th gauge 50 stitches 196,500/m² +/-10%

Accummen™, 75% recycled

BS EN 1307 Heavy Commercial Use Class 33

LC₂

Euroclass Bfl-s1

Tog Rating 0.39; ISO 8302: 0.04 m²K/W BS EN 985 Pass - suitable for continuous use

BS ISO 10361: Method B:2000 3 to 4

BS 4939: 1987 (2003) Recovery >80% (24hrs)

BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)


BS ISO 6356:2000 <2kV

BS EN ISO 105 - B02 Minimum Grade 6 BS 1006:UK-TB: 1990 Minimum Grade 4-5

BS EN 354:2003

BS EN ISO 10140-3:2010 23dB BS EN ISO 10140-3:2010 35.6dB

20 (5m²)





1

1



For best results we recommend



Î Î











*All tiles within these designs are unique and any linear aspects may not match from one tile to the next









111111





UKAS

Scheme Certificate Number





UKAS

BS EN ISO 9001:2015







Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling - on a scale from A+

Information Foundation. building materials with low emission class M1

environmental information

- Burmatex products achieve either A or A+ across all the BREEAM defined building applications For specific rating, please refer to www.breeam.co.uk
- Burmatex products qualify for SKA as they achieve one or more requested criteria
- All Burmatex carpet/carpet tile ranges are made at its single UK manufacturing site
- · Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of Burmatex Accummen™ backing comes from recycled materials

This floor covering was mad

- · Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- · All manufacturing waste is recycled and all electricity used is from renewable resources
- · All Burmatex products are heavy contract with a 10 year guarantee for maximum useful life
- Certified, Class A+: very-low VOC Emission

LEED® v4 - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/CI-v4 MRc2/MRc3 (Building product disclosure and optimization - environmental product declarations), MRc3/MRc4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/contact

Burmatex Ltd Victoria Mills, The Green Ossett, West Yorkshire WF5 OAN **United Kingdom**

T +44 (0) 1924 262 525 F +44 (0) 1924 280 033 UK email: projects@burmatex.co.uk

International email: international@burmatex.co.uk www.burmatex.co.uk

Burmatex reserves the right to improve the specification of all products without prior notification. E&OE

Burmatex carpets and carpet tiles should be installed and used in full accordance with instructions at www.burmatex co.uk and recognised trade standards.

Orders are subject to Burmatex terms and conditions of sale. See: www.burmatex.co.uk

LRV values for **tivoli mist**

Product code tiles	Product code planks	Product colour name	CIE Y	CIE L
32701	32901	south beach	14.27	44.89
32702	32902	palm springs	8.81	35.77
32703	32903	ocean drive	13.11	41.16
32704	32904	havana town	8.80	36.93
32705	32905	turtle bay	10.17	37.42
32706	32906	bora bora	14.24	43.03
32707	32907	baffin island	7.06	31.17
32708	32908	bergen city	4.69	24.36
32710	32910	icelandic isle	13.21	45.01
32711	32911	nordic fjord	7.47	33.95
32712	32912	polar drift	9.99	37.50
32713	32913	galapagos bay	5.75	27.32

LRV values for **tivoli**

Product code tiles	Product code planks	Product colour name	CIE Y	CIE L
20245	21145	dominica dawn	11.93	41.11
20242	21142	antigua steel	10.06	37.96
20207	21107	st lucia night	4.02	23.75
20275	21175	aruba dusk	7.02	32.03
20260	21160	st kitts basalt	2.91	19.68
20272	21172	cali coral	8.71	36.96
20267	21167	miami aqua	17.21	48.38
20269	21169	purple sky	9.10	36.18
20201	21101	guyana moss	9.06	36.10
20208	21108	belize greige	12.13	41.43
20268	21168	sri lanka sands	17.62	47.50
20253	21153	key west blue	2.69	18.77
20220	21120	barbados blue	6.23	29.98
20265	21165	kythira blue	18.19	47.37
20263	21163	naxos breeze	8.24	34.20
20266	21166	tiki yellow	16.09	47.71