

MADE IN THE UK. MADE TO LAST.

Specification

PRODUCT	Hobnail Heavy Contract Carpet and Tiles
FIBRE CONSTRUCTION	80% Polypropylene, 15% Polyamide, 5% Recycled Polyester
WEIGHT	1020gsm (Sheet), 3670gsm (Tile)
THICKNESS	7.20mm (Sheet), 8.0mm (Tile)
ROLL WIDTH	2 metre
TILE SIZE	50cm x 50cm (Tiles are Bitumen backed)
TILES PER BOX	20 (5m²)
COLOUR FASTNESS	Light (BS EN ISO 105:B02) >6 Wet Rubbing (BS EN ISO 105:X12) 5 Dry Rubbing (BS EN ISO 105:X12) 5
FLAMMABILITY	(BS5287) Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char
BS EN 13501	Class Cfl-s1 (Sheet) Class Bfl-s1 (Tile)
REDUCTION IN IMPACT NOISE	BS EN ISO 10140-3:2010: 25dB (Sheet)
ANTISTATIC	Suitable for use in computer rooms
INSTALLATION A + Tiles	Hobnail tiles should be laid tessellated as per the icon provided. The method of installation should conform to BS5325. For details of subfloor preparation and a full guide to installation visit www.heckmondwike-fb.co.uk. Before laying Hobnail, tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels.
ADHESIVE GUIDE	Sheet carpet can be fully adhered with F.Ball's F3 or F52, or Bostik Laybond Adhesive. Sheet carpet can also be laid into F. Ball's F40 as a release system. For tiles and planks, use F.Ball's F41 or Bostik Laybond Carpet Tile Tackifier.
MAINTENANCE	To achieve maximum life expectancy it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: www.heckmondwike-fb.co.uk

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Heckmondwike reserves the right to change or modify product specifications without giving prior notice.



EN 14041 Heckmondwike FB Liversedge WF157FH

Hobnail Sheet Fibre Bonded Sheet Floorcovering intended for internal use

13







EN 14041 Liversedge WF157FH

09

Hobnail Tile Fibre Bonded Tile Floorcovering intended for internal use























