

QUALITY
ORDER CODE

DATE: 25/04/2022
REPLACES: 22/01/2020

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

FAIRFIELD SILK ELITE SB
FSE

± 400 & 500
COLLECTION
1/10" TWIST

SOLUTION DYED

ECCELENA SILK 2-PLY

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.870
± 2.860

± 10,5
± 13,0
± 165.480
± 39,40
± 42,00

±
±

± 25
PILE IN

✓
✓

✓

NO SHOCK
✓

D0D89B5B

Cl. 23
Domestic Heavy



LC5





Efl



LOW RADIUS


Heavy non-domestic

QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8	± 25	
THERMAL RETENTION	(±) m²K/W	ISO 8302	± 0,15	
TOG rating	(±)		± 1,5	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356	≤	
LIGHTFASTNESS		ISO 105-B02	≥ 5	
RUBBINGFASTNESS DRY		ISO 105 X12	≥ 3-4	
RUBBINGFASTNESS WET		ISO 105 X12	≥ 3	
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01	≥ 3-4	
WATERFASTNESS STAINING		ISO 105-E01	≥ 2-3	

FAIRFIELD SILK ELITE SB

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

COLOURS

AVAILABLE FROM

AVAILABLE FROM

<u>SB 400</u>	FSE	<u>SB 500</u>
0221	ACORN 1	0221
0250	MAGNOLIA	0250
0253	MAGNOLIA 3	0253
0260	CAMEL	0260
0413	LEATHER 3	0413
0423	CORNSTALK 3	0423
0433	BAMBOO MAT 3	0433
0440	IVORY	0440
0663	CELADON 3	0663
0723	BLUE CAPE 3	0723
0750	SKY	0750
0810	CHARCOAL	0810
0820	SLATE	0820
0843	MOONSHINE 3	0843
0850	MOONBEAM	0850

<u>SB 400</u>	FSE	<u>SB 500</u>



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(15)

(15)