




Specification

PRODUCT	Dreadnought Heavy Contract Fibre Bonded Carpet and Tiles
FIBRE CONSTRUCTION	90% Polypropylene, 10% Recycled Polyester
WEIGHT	1495gsm (Sheet), 3995gsm (Tile)
THICKNESS	11mm (Sheet), 11.50mm (Tile)
ROLL WIDTH	2 metre, ribbing runs diagonally down length of roll
TILE SIZE	50cm x 50cm (Tiles are Bitumen backed)
TILES PER BOX	16 (4m²)
COLOUR FASTNESS	Light (BS EN ISO 105:B02) >6 Wet Rubbing (BS EN ISO 105:X12) 5 Dry Rubbing (BS EN ISO 105:X12) 5
FLAMMABILITY	(BS6307) Methenamine Pill Test - Pass
BS EN 13501	Class Efl (Sheet) Class Efl (Tile)
INSTALLATION Tiles	Dreadnought tiles should be laid tessellated as per the icon provided. The method of installation should conform to BS5325. For details of subfloor preparation and a full guide to installation visit www.heckmondwike-fb.co.uk. Before laying Dreadnought, tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels.
ADHESIVE GUIDE	Sheet carpet should be fully adhered with F. Ball F3 or Bostik Laybond Carpet Adhesive. For tiles use F. Ball F41 Tackifier or Bostik Laybond Carpet Tile Tackifier.
MAINTENANCE	To achieve maximum life expectancy it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: www.heckmondwike-fb.co.uk

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Heckmondwike reserves the right to change or modify product specifications without giving prior notice.





Heckmondwike FB

09

Dreadnought Sheet Floorcovering







Heckmondwike FB

Dreadnought Tile Fibre Bonded Tile Floorcovering





















11/22