VEBE FLOORCOVERINGS

Vebe Floorcoverings bv
Inslag 12, 8281 JV
P.O. Box 11, 8280 AA
Genemuiden, The Netherlands

T (+31) 88 825 11 00
F (+31) 38 385 61 87
E info@vebe.net
W www.vebe.net

Strong 745 S-L

Manufacturing process	Needlefelt		ISO 2424
Type of surface	Flecked		
Surface aspect	Coarse Fibred		ISO 2424
Width	200 cm		
Backing	LV		ISO 2424
Pile yarn composition	100% dorix® PA		ISO 2424
Pile weight	650 g/m²		
Total weight	1450 g/m²	+/- 15%	ISO 8543
Total height	6,5 mm	+15% / -10%	ISO 1765
Overall use class	Commercial 33, Areas with heavy use		EN 1307
Luxury class	LC1		EN 1307
Castor chair suitability	Yes, permanent use		EN 985
Stair suitability	Yes, permanent use		EN 1307
Colour fastness to light	≥ 5		ISO 105-B02
Colour fastness to rubbing, wet and dry	≥ 4		ISO 105-X12
Colour fastness to water	≥ 4		ISO 105-E01
Dimensional stability	Shrinkage ≤ 1,2 %		ISO 2551
	Extension ≤ 0,5 %		ISO 2551
Electrostatic charging	< 2kV		ISO 6356
Vertical resistance	< 1,0x10⁸ Ω		ISO 10965
Impact sound protection ΔLW	21 dB		ISO 10140

Acoustical sound absorption αS — ISO 354

Hz	125	250	500	1000	2000	4000
αW	0,00	0,04	0,09	0,17	0,38	0,66

Evaluated sound absorptions grade αW	0.20		ISO 11654
Thermal resistance	0,11 m².K/W		ISO 8302
Slip resistance	> 0,3	Machine direction	EN 13893
	> 0,3	Crossdirection	EN 13893
Flammability	Bfl,s1 (Glued)		EN 13501-1
Prodis-ID (GuT)	1B30308A		www.pro-dis.info
Comments	Construction principle: The cavity of the access floor generates an overpressure, which is pressing the air evenly through the carpet all over the area.		
TÜV PROFiCERT product	Certificate number: 70 710 5617-2		

Floorsymbols

Certificates



ISO 9001:2015-certified processes
ISO 14001:2015-certified processes

2019-08-27