




| DESCRIPTION  |                 |                    |   |
|--|-----------------|--------------------|---|
| Total thickness  | EN ISO 24346    | mm                 | 2.00  |
|  | ASTM F386-02    | inch               | 0.08  |
| Weight   | EN ISO 23997    | g/sq.m             | 2790  |
| Width of sheet   | EN ISO 24341    | cm                 | 200   |
|  | -               | feet - inch        | 6'6"  |
| Length of sheet  | EN ISO 24341    | lm                 | 20  |
|  | -               | feet - inch        | 66'   |
| Coverage / roll  | -               | sq.ft              | 430.56  |
|  | -               | sq.m               | 40  |
| Tile size  | EN ISO 24342    | mm                 | 608 x 608 *   |
| Number of tiles per package  | -               | -                  | 20  |
| CLASSIFICATION   |                 |                    |   |
| Norm / Product specification   | -               | -                  | EN ISO 10581  |
|  | ASTM F 1913-04  | -                  | compliant   |
| European classification  | EN ISO 10874    | class              | 34 - 43   |
| Fire rating  | EN 13 501-1     | class              | B <sub>f1</sub> -s1   |
|  | ASTM E648-08    | class              | Class I   |
|  | CAN/ULC S102.2  | -                  | -   |
| Static electrical propensity   | EN 1815         | kV                 | < 2   |
| PERFORMANCE  |                 |                    |   |
| Type Binder content  | EN ISO 10581    | type               | I   |
| Dimensional stability  | EN ISO 23999    | %                  | sheet ≤ 0.40<br>tile ≤ 0.25   |
| Impact sound insulation  | EN ISO 717-2    | dB                 | 5   |
| Residual indentation (norm)  | EN ISO 24343-1  | mm                 | ≤ 0.10  |
| Residual indentation (average measured value)                                      | -               | mm                 | ~ 0.02  |
| Castor chair test (type W)   | ISO 4918        | -                  | OK  |
| Thermal conductivity   | EN ISO 10456    | W/(m.K)            | 0.25  |
| Colour fastness  | EN 20 105 - B02 | degree             | ≥ 6   |
| Surface treatment  | -               | -                  | Evercare™   |
| Chemical products resistance   | EN ISO 26987    | class              | OK  |
| Anti-bacterial activity<br>(E.coli – S. aureus – MRSA) **                          | ISO 22196       | -                  | > 99 %<br>inhibits growth   |
| Anti viral activity (human coronavirus<br>229E)                                    | ISO 21702       | -                  | 99.7% after 2h  |
| ENVIRONMENT / INDOOR AIR QUALITY   |                 |                    |   |
| TVOC after 28 days   | ISO 16000-6     | µg/ m <sup>3</sup> | < 10  |
| Certification  | -               | -                  | Floorscore®   |
| CE MARKING   |                 |                    |   |
|  | EN 14041        | -                  |  |
|  |                 | -                  |  |

\* Products available in tiles for a minimum quantity order of 500 sqm

\*\* The implementation of an effective cleaning method is the best defence against infection